

AIRLESS AIR OPERATED PUMP

SMB CODE	SK451-000	TECHNICAL SPECIFICATIONS		OPTIONS
	FLUID PRESSURE RATIO	45:1		
	DELIVERY	3.98 (16) gpm (liter/min)		
	Recommended maximum speed	60 cycle/min		
	AIR MOTOR EFFECTIVE DIAMETER	10 (254) inch (mm)		PAINT HOSE 1/4" X 1.8M
	STROKE	120mm		
	MAX. INLET PRESSURE	100 (7) psi (BAR)		PAINT HOSE 3/8" X 15M
	MAX. OUTLET PRESSURE	4500 (310) psi (BAR)		HP NIPPLE 3/8" X 1/4"
	AIR INLET SIZE	3/4" (PT)		
	FLUID INLET SIZE	1-1/4" (PT)		SMB-235460 GUN
	TYPICAL FLUID HANDLED	EPOXY, ALKYD, URETHANE ANTICORROSIVE PRIMER HIGH VISCOSITY		SWITCH TIP (200-XXX) SWITCH TIP GUARD
	APPLICATION	ROOFING, PROTECTIVE COATING CONSTRUCTION, METAL STRUCTURE HIGH VISCOSITY COATING		
	WEIGHT			
SMB CODE	SK561-000	TECHNICAL SPECIFICATIONS		OPTIONS
	FLUID PRESSURE RATIO	56:1		
	DELIVERY	3.43 (13) gpm(liter/min)		
	Recommended maximum speed	60 cycle/min		
	AIR MOTOR EFFECTIVE DIAMETER	10 (254) inch (mm)		PAINT HOSE 1/4" X 1.8M
	STROKE	120mm		
	MAX. INLET PRESSURE	100 (7) psi (BAR)		PAINT HOSE 3/8" X 15M
	MAX. OUTLET PRESSURE	5600 (386) psi (BAR)		HP NIPPLE 3/8" X 1/4"
	AIR INLET SIZE	3/4" (PT)		
	FLUID INLET SIZE	1-1/4" (PT)		SMB-235460 GUN
	TYPICAL FLUID HANDLED	EPOXY, ALKYD, URETHANE ANTICORROSIVE PRIMER HIGH VISCOSITY		SWITCH TIP (200-XXX) SWITCH TIP GUARD
	APPLICATION	ROOFING, PROTECTIVE COATING CONSTRUCTION, METAL STRUCTURE HIGH VISCOSITY COATING		
	WEIGHT			
SMB CODE	SK681-000	TECHNICAL SPECIFICATIONS		OPTIONS
	FLUID PRESSURE RATIO	68:1		
	DELIVERY	2.86 (10.8) gpm (liter/min)		
	Recommended maximum speed	60 cycle/min		
	AIR MOTOR EFFECTIVE DIAMETER	10 (254) inch (mm)		PAINT HOSE 1/4" X 1.8M
	STROKE	120mm		
	MAX. INLET PRESSURE	100 (7) psi (BAR)		PAINT HOSE 3/8" X 15M
	MAX. OUTLET PRESSURE	6800 (469) psi (BAR)		HP NIPPLE 1/4" X 1/4"
	AIR INLET SIZE	3/4" (PT)		
	FLUID INLET SIZE	1-1/4" (PT)		SMB-235460 GUN
	TYPICAL FLUID HANDLED	EPOXY, ALKYD, URETHANE ANTICORROSIVE PRIMER HIGH VISCOSITY		SWITCH TIP (200-XXX) SWITCH TIP GUARD
	APPLICATION	ROOFING, PROTECTIVE COATING CONSTRUCTION, METAL STRUCTURE HIGH VISCOSITY COATING		
	WEIGHT			